


Z1188-ST-77

LARGE CAPACITY OIL INTERCEPTOR W/ INTEGRAL STORAGE TANK, HEAVY-DUTY TRAFFIC

SPECIFICATION SHEET

TAG



250 [946]	5 [127]	445 [1685]	3100 [1406]	47[1194]	36[914]	75 1/2[1918]	106 3/4 [2712]	40 3/4[1035]	32 1/2[825]	
ENGINEERING SPECIFICATION : ZURN Z1188-ST-77 Acid Resistant Coated interior and exterior fabricated steel oil interceptor, with bronze										
cleanout plug and visible double wall trap seal, removable combination pressure equalizing/flow diffusing baffle and sediment bucket, oil										
draw-off, ve	nt connec	ctions, and lef	t hand integral	storage tank. F	Provided with fo	our secured, gas	sketed heavy-du	ty traffic covers r	ated at 10,000	
lbs [4536 kg	g] maxim	um safe live l	oad, one havi	ng a 4 [102] cl	eanout access	port. Complet	te with electronic	c oil level float se	ensor, display	

box with audio and visual alarms, junction box, and flow control fitting. Regularly furnished with inlet and outlet in high position. Note: location

D/E

C

OPTIONS (Check/specify appropriate options)

		_		v	-
\mathbf{r}	ĸ	-	H	×	->

GPM [L]

Min.

Outlet

Size**

Ζ Acid Resistant Coated Fabricated Steel*

of outlet from bottom of interceptor cannot be changed.

Capacity

Gal. [L]

Wt.

Lbs. [kg]

SUFFIXES

Integral Acid Resistant Coated interior and exterior fabricated steel extension section. (Specify 'C' Dim. required) for _ -E recessed installation.

-K Anchor flange 1 3/4 [44] down from top and 2 [51] wide.

-KC Anchor flange 1 3/4 [44] down from top and 2 [51] wide with clamp collar.

Storage tank on right hand side when facing the inlet. -STR

> REV. DATE: 10/25/07 C.N. NO. 97524

Н

J

DWG. NO. P-15482 PRODUCT NO. Z1188-ST-77

*REGULARLY FURNISHED UNLESS OTHERWISE SPECIFIED