


Z1170-141 SIZE 700 GREASE INTERCEPTOR W/Ø4 [102] INLET AND OUTLET

SPECIFICATION SHEET

TAG

Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice



	Inlet/	Flow Rate	Capacity		Approx.	Dimensions in Inches			
Size	Outlet	G.P.M.	Water	Grease	Wt. Lbs.				
	Size*	[L]	Gal. [L]	Lbs. [kg]	[kg]	С	D/E	F	G
700	4 [102]	35 [132]	30 [113]	70 [32]	151 [68]	18-3/4 [476]	14-3/4 [375]	34-1/8 [867]	22-1/2 [572]

ENGINEERING SPECIFICATION: ZURN Z1170-141

Acid Resistant Coated interior and exterior fabricated steel grease interceptor, PDI, rated at 35 GPM [113] and 70 Lbs. [32kg] grease capacity, with internal air relief by-pass, bronze cleanout plug, removable pressure equalizing/flow diffusing inlet baffle, fixed bottom outlet baffle, and visible double wall trap seal. Gasketed non-skid secured cover complete with center tie down assembly, with Z1108 flow control fitting. Regularly furnished with a high inlet and outlet connection. Note: Location of outlet from bottom of interceptor cannot be changed.

PREFIXES

- Z Acid Resistant Coated Fabricated Steel*
 - ZS All Type 304 Fabricated Stainless Steel

SUFFIXES

- ____ -AL Aluminum Cover
- -DI Dual High/Low Inlet.
- -E Acid Resistant Coated Interior and exterior fabricated steel extension section. (Specify 'C' Dim. required) for recessed installation.
- -HD Heavy Duty Cover rated at 10,000 lbs. [4536 kg] maximum safe live load. A 3 [76] minimum extension height is required when Heavy-Duty Cover (-HD) option is specified.
- -K Anchor flange 1-3/4 [44] down from top and 2 [51] wide. A 3 [76] minimum extension height is required when anchor flange (-K) option is specified.
- -KC Anchor flange 1-3/4 [44] down from top and 2 [51] wide with clamp collar. A 3 [76] minimum extension height is required when anchor flange (-K) option is specified.
- _____ -L Angle type (Z1108-L) flow control device with plunger.
- -R Acid resistant coated interior and exterior fabricated steel recessing receiver for recessed installation is equipped with adjustable support brackets and gasketed non-skid cover with covered recessed lift handle.
- -RE Acid resistant coated interior and exterior fabricated steel recessing receiver enclosed type for recessed installation. Furnished with adjustable support brackets and gasketed non-skid cover with covered recessed lift handle.
- _____ -T Cover recessed for tile/terrazzo. A 3 [76] minimum extension height is required. (Specify recess depth 1/8 [3], 3/4 [19], or 1-1/4 [32]).

	REV. A	DATE: 04/20/	12 C.N. NO. 124167
*REGULARLY FURNISHED UNLESS OTHERWISE SPECIFIED	DWG.NO.	309051 P	RODUCT NO. Z1170-141
ZURN INDUSTRIES, LLC		•	ie, PA 16514

In Canada: ZURN INDUSTRIES LIMITED + 3544 Nashua Drive + Mississauga, Ontario L4V1L2 + Phone: 905\405-8272 Fax: 905\405-1292