


Z1186-ST-107 SIZE 700 OIL INTERCEPTOR W/ INTEGRAL STORAGE TANK, DOUBLE WALL CONTAINMENT, AND OIL LEVEL SENSOR

SPECIFICATION SHEET

TAG



Dimensions in inches [mm]								Oil Storage Tank Capacity	No. of
SIZE	С	D/E	F	G	н	К	N	Gal.[L]	Covers
700	22 3/4 [578]	12 7/16 [316]	43 7/16 [1103]	45 [1143]	23 1/4 [591]	16 3/4 [425]	37 [940]	55 [208]	3

ENGINEERING SPECIFICATION: ZURN Z1186-ST-107

Acid Resistant Coated interior and exterior fabricated steel oil interceptor, with bronze cleanout plug, visible double wall trap seal, removable combination pressure equalizing/flow diffusing baffle and sediment bucket, adjustable oil draw-off gate plate, vent connections and left-hand integral storage tank. Complete with double-wall containment, secured gasketed non-skid cover, and flow control fitting. Fiberglass sensor box contains a float oil level sensor. Fiberglass display box contains one green power light, one red oil light, audible alarm and junction box. Regularly furnished with inlet and outlet in high position. Note: location of outlet from bottom of interceptor cannot be changed.

OPTIONS (Check/specify appropriate options)

PREFIXES

Z SUFFIXES	Acid Resistant Coated Fabricated Steel*		all construction will extend the overall length of the unit by 3 [76] per side and increase	
HD STR	Heavy duty traffic cover rated at 10,000 lbs. maximum safe live load Storage tank on right hand side when facing the inlet.	the overall depth by 3 [76]. 2. Power supply 120V GFCI.		
* Regularly furni	shed unless otherwise specified.			
Zurn Industries.	LLC Specification Drainage Operation		Bey -	

Zurn Industries, LLC | Specification Drainage Operation 1801 Pittsburgh Avenue, Erie, PA U.S.A. 16502 · Ph. 855-663-9876, Fax 814-454-7929 In Canada | Zurn Industries Limited 3544 Nashua Drive, Mississauga, Ontario L4V 1L2 · Ph. 905-405-8272, Fax 905-405-1292 WWW.ZURD.COM