




Z1188-ST-79

LARGE CAPACITY OIL INTERCEPTOR W/ INTEGRAL STORAGE TANK & 4 [102] INLET / OUTLET

SPECIFICATION SHEET

TAG _____

Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice



HEX HEAD SET SCREW— REMOVE SCREWS TO USE LIFT HANDLES, REPLACE SCREWS ONCE COVER IS IN PLACE AND HANDLES ARE REMOVED.

Flow Rate GPM [L] Min.	Oil Storage Tank Cap. Gal. [L]	No. of Covers	
		Trap	Tank
75 [284]	125 [473]	1	1

Flow Rate GPM [L] Min.	Inlet/ Outlet Size**	Water Capacity Gal. [L]	Approx. Wt. Lbs. [kg]	Dimensions in Inches					
				C	D/E	F	G	H	J
75 [284]	4 [102]	88 [333]	615 [279]	22 3/4 [578]	18 1/2 [470]	51 3/8 [1305]	65 3/8 [1661]	29 1/4 [743]	15 1/2 [394]

ENGINEERING SPECIFICATION: ZURN Z1188-ST-79 Acid Resistant Coated interior and exterior fabricated steel oil interceptor, with bronze cleanout plug and visible double wall trap seal, removable combination pressure equalizing/flow diffusing baffle and sediment bucket, oil draw-off, vent connections, secured gasketed non-skid cover, complete with flow control fitting and left hand integral storage tank. Regularly furnished with 4 [102] inlet and outlet in high position. Note: location of outlet from bottom of interceptor cannot be changed.

OPTIONS (Check/specify appropriate options)

PREFIXES

___ Z Acid Resistant Coated Fabricated Steel*

SUFFIXES

- ___ -E Integral Acid Resistant Coated interior and exterior fabricated steel extension section. (Specify 'C' Dim. required) for recessed installation.
- ___ -HD Heavy-duty traffic cover rated at 10,000 lbs. maximum load. An increased 'C' dim. is required when -HD option is specified. (See -HD option specification sheet)
- ___ -K Anchor flange 1 3/4 [44] down from top and 2 [51] wide. A 3 [76] minimum extension height is required when anchor flange (-K) option is specified. (Specify 'C' Dim. height required.)
- ___ -KC Anchor flange 1 3/4 [44] down from top and 2 [51] wide with clamp collar.
- ___ -STR Storage tank on right hand side when facing the inlet.

REV.	DATE: 9/25/08	C.N. NO. 99144
DWG. NO. P-15605	PRODUCT NO. Z1188-ST-79	

*REGULARLY FURNISHED UNLESS OTHERWISE SPECIFIED