


## ZA880-300/340-TG-100

## 3[76] WIDE DECORATIVE TILE-INLAY GRATE

Dimensional Data (Imperial and [Metric]) are subject to manufacturing tolerances and change without notice. Linear (in[mm]), Area (in²[mm²], & Weight (Ibs[kg]).

Please	Item	Part	Item
Check	No.	Number	I.D.
	1	312483	ZA880-300/340-TG-100



AZ GRATE ENGINEERING SPECIFICATION: Zurn 2-7/8" [74mm] wide Tile-Inlay Grate. Aluminum grate conforms to ASTM B-209 (Type UNS A91100). Tile-Inlay grate is rated class Aper the DIN EN1433 top load classifications. Supplied in 48" [1219mm] lengths with 3/4" [19mm] bearing depth. Grate has an open area of 2.87 in<sup>2</sup> per foot [61 cm<sup>2</sup>/m]. Grate shall be produced in the U.S.A.



TG - Aluminum Decorative				
Material:	Aluminum			
DIN Rating:	Class A			
Weight: .45 lbs/ft. [0.67 kg/m]				
Open Area: 2.87 in <sup>2</sup> /ft. [61cm <sup>2</sup> /m]				
ANSI Rating: Light-Duty				
Application: Tile-Inlay				
ADA:	Yes			
H-20:	No			
FAA:	No			

Zurn Industries, LLC | Specification Drainage Operation 1801 Pittsburgh Avenue, Erie, PA U.S.A. 16502 · Ph. 855-663-9876, Fax 814-454-7929

In Canada | Zurn Industries Limited

www.zurn.com

3544 Nashua Drive, Mississauga, Ontario L4V 1L2 · Ph. 905-405-8272, Fax 905-405-1292

Rev.

Date: 12/06/2018 C.N. No. 140900

Prod. | Dwg. No. ZA880-300/340-TG-100