


Z415I-79

BODY ASSEMBLY W/ "TYPE I" STRAINER, WEEP HOLES & S.S. SECURED MESH SCREEN

SPECIFIC	ATION SHEET
TAG	

Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice



Dimensions In Inches								Strainer
A - Pipe Size	B Strainer Dia.	С	k	(K	(1	Wt. Lbs.	Open Area Sq. In. [Cm ²]
A - 1 ipc dizc			Min.	Max.	Min.	Max.	[Kg.]	
2-3 [51-76]	5 [127]	3/4 [19]	1 5/8 [41]	2 3/4 [70]	2 1/2 [64]	3 1/2 [89]	14 [6]	8 [52]
2-3-4 [51-76-102]	7 [178]	1 [25]	2 1/4 [57]	2 3/8 [60]	3 1/8 [79]	4 1/4 [108]	19 [9]	13 [84]
3-4 [76-102]	9 [229]	1/2 [13]	2 [51]	3 [76]	2 7/8 [73]	4 [102]	23 [10]	23 [148]
6 [152]	9 [229]	1/2 [13]	2 [51]	2 7/8 [73]	2 7/8 [73]	4 [102]	23 [10]	23 [148]

ENGINEERING SPECIFICATION: ZURN ZN415I-79 Floor and shower drain, Dura-Coated cast iron body with bottom outlet, combination invertible membrane clamp and adjustable collar with "TYPE I" polished nickel bronze strainer with raised flange and eight (8) 1/4 [6] diameter weep holes with stainless steel secured mesh screen.

OPTIONS (Check/specify appropriate options)

PIPE SIZE 2 thru 4 [51 th 2 [51] 3 [76] 4 [102] 6 [152] 2 thru 4 [51 th 2 thru 4 [51 th	ru 102]	OUTLET	(Spec IC IP IP IP IP NH NL	sify size/typ Inside Ca Threaded Threaded Threaded Threaded No-Hub Neo-Loc			3 7/ 2 3/ 2 5/ 2 7/ 2 3/ 3 7/	DDY HT.DIM. /8 [98] /8 [60] /8 [67] /8 [73] /4 [70] /8 [98] /8 [117]
	D.C.C.I. Body Assembly w/ F D.C.C.I. Body Assembly w/ F			•	p*			
SUFFIXES			V	0 90° Th	ater Valve readed Sid , 3 [76] onl	le Outlet Body y)		
	FURNISHED UNLESS OTHERWISE	·	D		REV.B DWG.NO		03/11/04 PRODUC	C.N. NO. 92018 CTNO. Z415I-79