




Z-1188-114

LARGE CAPACITY OIL INTERCEPTOR

SPECIFICATION SHEET

TAG _____

Dimensions Subject to Manufacturing Tolerances All Dimensions in [] are in MM



Flow Rate GPM[L]Min	Inlet/Outlet Size**	Water Capacity Gal. [L]	App. Wt. Lbs. [Kg]	No. of Covers
150 [568]	4 [100]	190 [719]	888 [403]	2

ENGINEERING SPECIFICATION: ZURN Z-1188-114 Large capacity Acid Resistant Coated interior and exterior fabricated steel oil interceptor, with internal air relief by-pass, bronze cleanout plug and visible double wall trap seal, removable combination pressure equalizing/flow diffusing baffle and sediment bucket, horizontal baffle, adjustable oil drawoff and vent connections either side. Secured gasketed non-skid cover complete with flow control fitting. Regularly furnished with inlet and outlet in high position.

OPTIONS (Check/specify appropriate options)

PREFIXES

_____ Z- Acid Resistant Coated Fabricated Steel*

SUFFIXES

- _____ -E Acid Resistant Coated interior and exterior fabricated steel extension section. (Specify 'C' Dim. required) for recessed installation.
- _____ -HD Heavy duty traffic cover rated at 10,000 lbs [4536] kg. maximum safe live load.
- _____ -K Anchor flange 1 3/4 [44] mm down from top and 2 [51] mm wide. No extension required to accommodate -K.
- _____ -KC Anchor flange 1 3/4 [44] mm down from top and 2 [51] mm wide with clamp collar.

*REGULARLY FURNISHED UNLESS OTHERWISE SPECIFIED

REV.	DATE: 4/26/01	C.N. NO. 87624
DWG. NO. P-14826	PRODUCT NO. Z-1188-114	